


ANTLIA T LED

Spotlights



Images for the product family and options:



Description:

Track mounted LED downlight
Light distribution type: direct
Optical system: opal polycarbonate diffuser
Housing: aluminium
Colour: white (RAL9016), black (RAL9005)

General data:

Mains voltage: 220-240V, 0/50/60Hz
LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions)
SDCM: 3
Protection class IEC: I
Ingress protection code: IP20
Mechanical impact resistance: IK02
Operating temperature range, °C: ta 0...+35

Installation:

In 3-phase track. Track adaptor (3-phase + N) with phase selector

Environment:

Indoor

Application:

Retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Antlia T LED1x1450 D948 T830 OP	200	200	150	1382	11,7	118	80+	3000	1,00
Antlia T LED1x2000 D949 T830 OP	200	200	150	1936	16,2	120	80+	3000	1,00
Antlia T LED1x2700 D950 T830 OP	200	200	150	2635	23,0	114	80+	3000	1,00
Antlia T LED1x1450 D948 T840 OP	200	200	150	1443	11,7	123	80+	4000	1,00
Antlia T LED1x2000 D949 T840 OP	200	200	150	2023	16,2	125	80+	4000	1,00
Antlia T LED1x2700 D950 T840 OP	200	200	150	2753	23,0	120	80+	4000	1,00

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI Driver with DALI interface

*note - Stucchi tracks is not compatible with switch-control dimming

RAL9005 Black colour body and adaptor

T830 Colour temperature 3000K, CRI 80+

T840 Colour temperature 4000K, CRI 80+

